

**Semi-automatic Applicators affix labels
to a wide range of containers
Replaces Hand-Application**

AP-Serie
AP360e/362e



DEDRUMA

Etiketten • Drucker • Etikettierer • Scanner • Thermotransferfolien • Zubehör

Fast and accurate application of labels

The two applicators are compact, **semi-automatic labelling** device that makes it fast and easy to apply pressure-sensitive labels to bottles, cans, jars, tubes and many other cylindrical and tapered containers. Up to 1200 containers per hour is possible.

Labels are applied straight, without wrinkles or folds, in precisely the spot desired. This gives finished products a highly professional look and significantly increases the number of containers that can be labeled per hour versus manually applying labels.

Operation is simple: set the guides, place the container in the mechanism, press the footswitch and the label is applied. A wide range of products can be labeled including wine, water, beer, spirits and other beverages, sauces, nutraceuticals, vitamins, cosmetics, bath and spa products, spices, specialty foods, health and beauty care, oils, lotions, fragrances, chemicals, paint and much more.

AP360e is the base model and applies labels to the front of containers.

AP362e is an advanced model that includes front and back labelling with variable spacing, memory for up to nine jobs, and a counter with built-in LED display.

An integrated, spring-loaded pressure arm applies consistent downward pressure to securely affix labels even on very small radius containers such as lip balm tubes.

AP360e and AP362e are the perfect accessories to Primera's LX-Series and CX-Series color label printers. Together, they provide a complete print-and-apply solution that's perfect for a wide range of small to medium-sized businesses. Roll or fan-fed labels printed by other methods such as flexographic, offset and thermal transfer can also be applied with the applicators.

Setting up and operating the devices is quick and easy:

1. Adjust the guides
2. Place the container or bottle in the machine
3. Press the footswitch and your label will be applied

Technical details:

Container width:	24,4 mm - 238 mm
Container diameter:	15 mm - 170 mm
Container shape:	cylindrical and many tapered
Supply roll diameter:	to 203 mm
Media liner width:	25,4 mm - 213 mm
Supply roll core:	51,8 mm - 76,2 mm
Electrical rating:	12 VDC, 5 A
Power requirements:	100-240 VAC, 50/60 Hz, 60 Watt
Agency certifications:	UL, UL-C, CE, FCC class A
Weight:	7,26 kg
Dimensions:	340 mm W x 226 mm H x 328 mm D

